

* Guangzhou Harley Commodity Company Limited

Model: # L-288S TC-84A-9321 NIOSH 42 CFR part 84

USE INSTRUCTIONS

- 1. Failure to follow all instructions and limitations can seriously reduce the effectiveness of this respirator and could lead to illness, injury or death.
- 2. A properly selected respirator is essential. Before occupational use, the wearer must be trained by the employer in the correct use of the respirator in accordance with applicable safety and health standards.
- 3. This product does not supply oxygen. Use only in adequately ventilated areas containing sufficient oxygen to support life.
- 4. Discard the respirator in dustbin and replace with a new one if:
 - A. excessive clogging of the respirator causes breathing difficulty
 - B. the respirator becomes damaged.
- 5. Leave the contaminated area if dizziness, irritation or other distress occurs.
- 6. Keep respirators in the display box away from direct sunlight until use.
- 7. Before occupational use of this respirator, a written respiratory protection program must be implemented meeting all the local government requirements. In the United States, employers must comply with OSHA 29 CFR 1910.134 which includes medical evaluation, training, and fit testing.
- 8. Before wearing the respirator users must check whether there is crack or spot around the welding spot .if yes, the respirator must be discarded at once and can not be used again.

CAUTION AND LIMITIONS

- A Not for use in atmospheres containing less than 19.5 percent oxygen.
- B Not for use in atmospheres immediately dangerous to life or health.
- C Do not exceed maximum use concentrations established by regulatory standards.
- J Failure to properly use and maintain this product could result in injury or death.
- M All approved respirators shall be selected, fitted, used, and maintained in accordance with MSHA, OSHA, and other applicable regulations.
- N Never substitute, modify, add, or omit parts. Use only exact replacement parts in the configuration as specified by the manufacturer.
- O Refer to User's Instructions, and/or maintenance manuals for information on use and maintenance of these respirators.
- P NIOSH does not evaluate respirators for use as surgical respirator.

Donning & Fitting Instructions

1. Hold the respirator in hand and with the nosepiece at your fingertips. Allow headbands to hang freely below hand.

- 2.Cup the respirator firmly against your face with the nosepiece on the bridge of your nose.
- 3.Stretch and pull the lower headband over the head and position below your ears. Stretch and pull the top headband on the back of your head above your ears
- 4. Press soft metal or plastic nosepiece to conform snugly around your nose. Using both hands press the nose piece to conform snugly around the nose. Using only one hand may not ensure a uniform seal.
- Seal check:
 - To test the fit of a respirator without an exhalation valve, cup both hands over the respirator and exhale sharply.
 - To test the fit of a respirator with an exhalation valve, cup both hands over the respirator and inhale sharply. A negative pressure should be detected inside the respirator.
 - If air flow is felt in the nose area, re-adjust/tighten the nose clip.
 - If air flow is felt around the edges of the respirator, re-position the respirator/head strap to achieve a better fit.
- 6. Change the respirator immediately if breathing becomes difficult or respirator becomes damaged or distorted.
- 7. Change the respirator if a proper face seal can not be achieved.
- 8. Careful observance of these instructions is an important step in safe respirator use.
- 9. When you take off respirator, Remove up headband first, then remove down headband, and discard the respirator in the dustbin. Then wash your hands.









Protection:

- N-series filters are effective against particle aerosols free of oil.
- N95-Particulate Filter (95% filter efficiency level) effective against particulate aerosols free of oil.

Guangzhou Harley Commodity Company Limited

(Plant A01) Yuanzhougang Village, Taiping Town,

Conghua District, Guangzhou, China

TEL:0086-20-37512950

FAX:0086-20-37512951

WEB:www.kn95.net

EMAIL:sales@kn95.net